



主要特点 Main Features

微机控制和工业触摸屏显示有关参数。
特制的机架，强度高，易调整，便于大漏底的拆卸。

封闭式圆墙板避免了墙板堵花。

适应棉箱或双棉卷喂入。

可视的吸塑滤尘管道，光滑流畅，多点连续吸，压力连续检测，吸尘杂效果好。

盖板倒转，增强分梳，改善棉网质量。

前后固定盖板、棉网清洁器及分梳板。

锡林道夫结构优化设计，提高精度。

全新外观设计，美观大方。

前后固定盖板、棉网清洁器，采用铝型材，轻巧光洁，除杂效果好。

新型皮圈导棉，免维护，操作方便。

设长、短片段混合环自调匀整装置。

Microcomputer controls and touch screen display relative parameter.

The special workframe with high strength, easy to adjust and convenient to take out the under casing of the cylinder.

Scaled lateral shield of the cylinder to avoid the fly on it.

Suitable for chutes feed or two laps feed.

Visible plastic adhesive filtering pipe with smooth surface, multi suction point on card for continuous suction with good suction efficiency. Continuously pressure detection.

Reversed revolving flats increase carding action and improve web quality.

Front and post stationary flats, web cleaners and carding segment under licker-in are fitted.

Optimum designed constructions of the cylinder and doffer ensure its precision.

Newly designed profile with beautiful appearance.

Front and post stationary flats and web cleaners are made of aluminum with lightweight and smooth to ensure good suction efficiency.

New type cross apron for sliver guiding, free of maintenance, easy operation.

Long-term and short-term mixed loop autoleveller is equipped.